FABRAL

ALUMINUM BUILDINGSPRODUCT OFFERING



Fabral offers light-weight, non-corrosive, low maintenance aluminum roofing panels that are ideal for most agricultural applications. Fabral's aluminum panels not only are the best protection against highly corrosive animal waster but also the first that cones to mind when dealing with weather elements (ensures no edge rust). Fabral aluminum panels are made with 90% recyclable content and 100% recyclable reducing the need for using the earth's natural resources.









Fabrib[®]

Available in Idabel, OK and Tifton, GA Service Areas




48 Coverage with 9/16" Rib Height and 2 2/3" Center to Center

ALUMINUM FABRIB® LOAD-SPAN TABLES FOR ALUMINUM FABRIB® Allowable wind uplift loads (psf)

Thickness	Substrate	Fastener	9"	12"	15"	18"	21"	24"	30"	36"
.019*	7/16° OSB	#14 x 1" Stainless	111.4	83.5	66.8	55.7	47.7	41.7	33.4	27.8
.019*	1/2" Plywood	#14 x 1" Stainless	184.8	138.6	110.9	92.4	79.2	69.3	55.4	46.2
.019*	Solid 2x SPF	#10 x 1" Stainless	185.7	139.3	111.4	92.8	79.6	69.6	55.7	46.4
.021*	7/16" OSB	#14 x 1" Stainless	111.4	83.5	66.8	55.7	47.7	41.7	33.4	27.8
.021*	1/2" Plywood	#14 x 1" Stainless	184.8	138.6	110.9	92.4	79.2	69.3	55.4	46.2
.021*	Solid 2x SPF	#10 x 1" Stainless	267.4	200.5	160.4	133.7	114.6	100.2	80.2	66.8
		Screws/Square	251	188	153	132	118	104	83	76

Correct Fabrib® Sidelap





Strongrib®

Available in the Lancaster, PA Service Area



36" Coverage with 3/4" Rib Height and 9" Center to Center

ALUMINUM STRONGRIB®

LOAD-SPAN TABLES FOR ALUMINUM STRONGRIB® Allowable wind uplift loads (psf)

Thickness	Substrate	Fastener	9"	12"	15"	18"	21"	24"	30"	36"
.018*	7/16° OSB	#14 x 1" Stainless	99.5	74.6	59.7	49.7	42.6	37.3	29.8	24.8
.018*	1/2" Plywood	#14 x 1" Stainless	165.1	123.8	99.0	82.5	70.7	61.9	49.5	41.2
.018*	Solid 2x SPF	#10 x 1" Stainless	165.9	124.4	99.5	82.9	71.1	62.2	49.7	41.4
		Screws/Square	192	148	120	104	92	80	68	60

Correct Strongrib® Sidelap

BUTYL SEALANT LOCATION (OPTIONAL FIELD APPLIED) PURLIN BEARING LEG

Screw Pattern

INTERMEDIATE ROOF PURLINS AND ALL SIDING

PART TO THE TOTAL THE TO

Fabral's Aluminum Roofing & Siding is backed by our 30-Year Corrosion Guarantee.

Aluminum panels are available in custom lengths up to 16' in either mill or white finish.

AluTwin

Available in Idabel, OK and Tifton, GA Service Areas




48" Coverage with 7/8" Rib Height and 8" Center to Center

ALUTWIN

LOAD-SPAN TABLES FOR ALUMINUM ALUTWIN Allowable wind uplift loads (psf)

Thickness	Substrate	Fastener	9"	12"	15"	18"	21"	24"	30"	36"
.016"	7/16* OSB	#14 x 1" Stainless	74.6	56.0	44.8	37.3	32.0	28.0	22.4	18.6
.016"	½" Plywood	#14 x 1" Stainless	113.7	85.3	68.2	56.8	48.7	42.6	32.0	22.0
.016"	Solid 2x SPF	#10 x 1" Stainless	113.7	85.3	68.2	56.8	48.7	42.6	32.0	22.0
		Screws/Square	192	147	122	107	97	87	72	67

Correct AluTwin Sidelap



Screw Pattern

^†q._p^~q._p^~q._p^~p^~p ROOFING - EAVES, RIDGES, AND ENDLAPS ~~**-ROOFING - INTERMEDIATE SUPPORTS** SIDING - ALL SUPPORTS

2 1/2" Corrugated

Available in Idabel, OK, Lancaster, PA, Sacramento, CA, Spokane, WA, and Tifton, **GA Service Areas**



48" Coverage with 1/2" Rib Height and 2 2/3" Center to Center

ALUMINUM 2 1/2" CORRUGATED


LOAD-SPAN TABLES FOR ALUMINUM 2 1/2" CORRUGATED Allowable wind uplift loads (psf)

Thickness	Substrate	Fastener	9"	12"	15"	18"	21"	24"	30"	36"
.016"	7/16* OSB	#14 x 1" Stainless	112.0	84.0	67.2	56.0	48.0	42.0	33.6	28.0
.016"	1/2" Plywood	#14 x 1" Stainless	185.7	139.3	111.4	92.8	79.6	69.6	50.0	35.0
.016"	Solid 2x SPF	#10 x 1" Stainless	186.6	140.0	112.0	93.3	80.0	70.0	50.0	35.0
		Screws/Square	216	162	132	114	102	90	72	66

Correct 2 1/2" Corrugated Sidelap



Screw Pattern



Grandrib 3®

Available in Cedar City, UT, Grapevine, TX, Gridley, IL, Idabel, OK, Lancaster, PA, Marshfield, WI, Sacramento, CA, Spokane, WA, St. Joseph, MN, and Tifton, GA Service Areas



36" Coverage with 3/4" Rib Height and 9" Center to Center


Correct Grandrib 3[®] Sidelap PURLIN BEARING

ALUMINUM GRANDRIB 3®

LOAD-SPAN TABLES FOR .016" ALUMINUM GRANDRIB 3® ROOFING Allowable wind uplift loads (psf)

Thickness	Substrate	Fastener	9"	12"	15"	18"	21"	24"
.016°	7/16" OSB	#14 x 1" Stainless	99.5	74.6	59.7	49.7	42.6	37.3
.016°	½" Plywood	#14 x 1* Stainless	165.1	123.8	99.0	82.5	70.7	61.9
.016"	Solid 2x SPF	#10 x 1* Stainless	165.9	124.4	99.5	82.9	71.1	62.2
		Screws/Square	190	150	120	100	90	80

Screw Pattern



Cedar City, UT	800.432.2725	Marshfield, WI	800.528.0878
Grapevine, TX	800.477.9066	Sacramento, CA	800.733.5684
Gridley, IL	800.451.3974	Spokane, WA	800.456.9124
Idabel, OK	800.926.5809	St. Joseph, MN	800.873.3440
Lancaster, PA	800.477.2741	Tifton, ĠA	800.749.8144

800.477.2741