




Standard Stock Colors




Regal White
SR: .68 IE: .86 SRI: 82



Bone White
SR: .72 IE: .84 SRI: 87



Almond
SR: .63 IE: .86 SRI: 75



Sandstone
SR: .54 IE: .86 SRI: 63



Medium Bronze
SR: .30 IE: .87 SRI: 31



Dark Bronze
SR: .26 IE: .84 SRI: 24



Dove Gray
SR: .49 IE: .87 SRI: 56



Slate Gray
SR: .37 IE: .86 SRI: 39



Charcoal
SR: .32 IE: .85 SRI: 32




Matte Black
SR: .27 IE: .86 SRI: 26



Surrey Beige
SR: .40 IE: .86 SRI: 43



Classic Green
SR: .26 IE: .84 SRI: 24



Bright Silver Mica**
SR: .60 IE: .77 SRI: 68

Standard Non-Stock Colors



Sierra Tan
SR: .35 IE: .86 SRI: 37



Pewter**
SR: .36 IE: .85 SRI: 38



Mansard Brown
SR: .29 IE: .86 SRI: 29



Hemlock Green
SR: .28 IE: .87 SRI: 28



Hartford Green*
SR: .10 IE: .82 SRI: 2



Regal Blue*
SR: .28 IE: .86 SRI: 27



Banner Red^^
SR: .42 IE: .84 SRI: 45



Colonial Red
SR: .34 IE: .86 SRI: 35



Silversmith**
SR: .53 IE: .78 SRI: 59



Champagne^^**
SR: .37 IE: .83 SRI: 38



Patina Green
SR: .29 IE: .87 SRI: 29



Slate Blue
SR: .26 IE: .85 SRI: 24

SR = Solar Reflectivity
IE = Initial Emissivity
SRI = Solar Reflective Index

* Denotes Dark Colors ^^ Denotes Exotic Colors ** Features a pearlescent mica finish; subject to premium pricing.

†Spangle and Backer color may vary unless otherwise requested.

Colors shown are as close to actual colors as allowed by the printing process. Actual metalsamples are available. Colors may appear different when viewed at different angles and under different lighting conditions. Due to product improvements, changes and other factors, we reserve the right to change or delete information herein without prior notice.

ARCHITECTURAL PVDF				STEEL (GA)				ALUMINUM (in)	
FABRAL COLOR	SR	IE	SRI	24GA	24GA	24GA	22GA	.032	.040
Standard Coil Width				48.375"	43"	44.375"	44.375"	48.250"	48.250"
STANDARD STOCK COLORS	Regal White	.68	.86	82	✓	✓	✓	✓	
	Bone White	.72	.84	87	✓	✓	✓	✓	✓
	Almond	.63	.86	75	✓	✓	✓	✓	✓
	Sandstone	.54	.86	63	✓	✓	✓	✓	
	Medium Bronze	.30	.87	31	✓	✓	✓	✓	
	Dark Bronze	.26	.84	24	✓	✓	✓	✓	✓
	Dove Gray	.49	.87	56	✓	✓	✓	✓	
	Slate Gray	.37	.86	39	✓	✓	✓	✓	
	Charcoal	.32	.85	32	✓	✓	✓	✓	✓
	Matte Black	.27	.86	26	✓	✓	✓	✓	✓
	Surrey Beige	.40	.86	43	✓	✓	✓	✓	
	Classic Green	.26	.84	24	✓	✓	✓	✓	
	Bright Silver **	.60	.77	68	✓	✓	✓	✓	
	Bare Galvalume	N/A	N/A	N/A	✓	✓	✓	✓	
STANDARD NON-STOCK COLORS	Slate Blue	.26	.85	.24					
	Sierra Tan	.35	.86	37					
	Pewter**	.36	.85	38					
	Mansard Brown	.29	.86	29					
	Hemlock Green	.28	.87	28					
	Hartford Green*	.10	.82	2					
	Regal Blue*	.28	.86	27					
	Banner Red^^	.42	.84	45					
	Colonial Red	.34	.86	35					
	Silversmith**	.53	.78	59					
	Champagne^^ **	.37	.83	38					
	Patina Green	.29	.87	.29					

PAINT PERFORMANCE PROPERTIES	HOT-DIPPED GALVANIZED STEEL OR GALVALUME®	ALUMINUM
Accelerated Weathering ASTM D 4587 (Drew Cycle Weatherometer) ASTM G 23	Hours: 3,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max	Hours: 3,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 Δ E Hunter units max
Salt Spray ASTM B 117	Hours: 1,000 Total Scribe: Rating 7 1/8" (1.6mm) Field: Rating 10, no blisters	Hours: 3,000 Total Scribe: Rating 10, no creepage Field: Rating 10, no blisters
Humidity ASTM D 2247	Hours: 2,000 Total Rating: 10, No blisters	Hours: 3,000 Total Rating: 10, No blisters
Formability ASTM D 4145	0T-3T	0T-3T
ASTM D 522 (Elongation over 1/8" mandrel)	No cracking No loss of adhesion	No cracking No loss of adhesion
Pencil Hardness ASTM D 3363	HB-2H	HB-2H
Abrasion Resistance ASTM D 968	55-75 Liters of falling sand	55-75 Liters of falling sand
Specular Gloss ASTM D 523	20-35 at 60°	20-35 at 60°
Reverse Impact ASTM D 2794	2x Metal thickness in inch-lbs No loss of adhesion	1 1/2x Metal thickness in inch-lbs No loss of adhesion
Flame Test ASTM E 84	Class A-rated coating	Class A-rated coating

Due to product improvements, changes and other factors, we reserve the right to change or delete information herein without prior notice.

- ✓ Stocked Color
- * Denotes Dark Colors
- ^^ Denotes Exotic Colors
- ** Features a pearlescent mica finish; subject to premium pricing

NOTES ON AVAILABILITY:

- For availability on products, colors, gauges and coil widths, please contact your Fabral Sales Representative.
- Standard inventory is non-embossed. Please contact us for the availability of stucco embossing.
- Protective, strippable film is available upon request.
- Mica colors are subject to premium pricing. Due to the unique effect of the Mica finishes, appearances may vary from batch to batch.
- Bare Galvalume, special paint systems and coating systems are available. Please contact your Fabral Sales Representative for details.
- All colors are supplied in Medium Gloss (20-35 at 60°). Low Gloss available and subject to minimum coating run.
- Subject to change without notice.
- Fabral standard architectural colors and finishes feature 70% polyvinylidene fluoride (PVDF) resin paint systems to ensure long-term color retention and performance. Custom colors and finishes are also available. Minimum quantities and set-up charges may apply.
- Order Minimums: Non-stock standard color orders must meet minimum coating requirements. Please contact your Fabral Sales Representative