

CONDENSTOP CHEMICAL RESISTANCE

Stop condensation with Fabral factory applied CondenStop. Easily and effectively prevent condensation and the problems caused by condensation by installing Fabral panels featuring Condenstop on your next project.

Microspheres

The chemical resistance has been tested by immersion for fourteen days in pure (100%) solutions. The chemical resistance is classified as either 1, 2, or 3.

1 indicates no unfavorable effect, 2 indicates that care should be taken to avoid exposure for longer periods or at high temperatures, and 3 indicates that contact with high concentrations should be avoided.

Solvent	Class
Toluene	1
Styrene	1
Methanol	3
Ethanol	3
Iso-Propanol	1
Ethylene Glycol	1
Ethylacetate	2(1)
N-Hexane	1
Acetone	3
MEK, 2-Butanone	3
10% NaCl	1
10% NaOH	2(1)
10% H ₂ SO ₄	1

Note: The use of or exposure to any solvents should, in general, be avoided for health reasons and to protect metal, coating and CondenStop.

Hotmelt Adhesive

The resistance of the adhesive against common disinfectants has been tested by immersion for 24 hours in the following solutions. In no case was any long term effect of the exposure detrimental.

Disinfectant

5% Bleach (Hypochlorite)

10% Alcohol/MEK

5% Sodium Lauryl Sulphate (Soap)

5% Dettol (Chloride Phenol)

5% Hydrogen Peroxide

Note: Special care should be taken when using any disinfectant. Always use the services of a qualified professional and test the disinfectant to be used on a small area to verify its effect on CondenStop. Under no circumstance should high pressures or hard brushes be used to apply disinfectants.

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability, safety, suitability any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. Values and opinions presented in this document are obtained from suppliers and by using listed and unlisted methods. Data are subject to normal variations and are subject to change without notice. The most recent version of this document supersedes all previous versions. All rights reserved.