

SELECT SERIES® 12

PRODUCT SPECIFICATIONS



Electronic Theatre Controls, Middleton, WI

12-R2 11/2* 12-R0 11/2* 12-RW 11/2*





CONCEALED FASTENER WALL PANEL

Fabral Select Series® 12, a classic concealed fastener flush panel design, provides a range of profiles and configurations for architectural, commercial, and industrial applications. With three options, architects and designers have the ultimate design versatility in a wall panel, fascia, or soffit application. The Select Series® 12 panels can be mixed with Select Series® 612 for varying design elements, demonstrating a unique approach to using metal.













SELECT SERIES® 12

PRODUCT SPECIFICATIONS



DESIGN INFORMATION

- Perforation Available Upon Request
- Panel Ends Can be Swedged for End Laps
- Panel Length: Maximum 45' Minimum 4'
- Panel Width: 12"

WARRANTY COVERAGE

Fabral® provides a 30-year paint-finish warranty against cracking, chipping, peeling, fading, and chalking, providing confidence in a long-lasting application.

To Ensure the Durability of Select Series® 12 Panels:

- 1. Use proper care.
- 2. Remove filings, grease, stains, marks, or excess sealants from the roof panel system to prevent staining.
- 3. Store panels and flashings in a safe, dry environment.

PRODUCT DESCRIPTION

Acceptable Product: Fabral® Select Series® 12

Air Infiltration: ASTM E283 0.10 cfm/ft² @ 1.57 psf

0.25 cfm/ft² @ 6.24 psf No Water Leakage @ 12 psf

Class 90, #244

Water Penetration: ASTM E331

Wind Uplift: UL580

Class 4 Impact: UL2218
Class A Fire: UL790

PRODUCT INSTALLATION

Select Series® 12 panels are recommended for siding or soffits only. The panels should only be installed vertically when used for wall applications. Install panels that are plumb, level, and straight so they are watertight and without waves or other distortions, allowing for thermal movement considerations. Sealant tape or caulking should be applied at flashing and panel joints to prevent water penetration.









