

Technical Bulletin

CLASS A FIRE RATINGS AND UL 2218 HAIL IMPACT RATING

Fabral has a Class A fire rating and a class 4 hail impact rating by UL2218 for the following coated steel and aluminum panels: as "AT Panel" (Alutuff), "Grandrib 3", "Grandrib 3 PLUS", "1-1/2 in. SSR", "AVALON", "Slim Seam", "Stand'N Seam", "Mighti-Rib", "Ultra-Rib", "V-Crimp", "Hefti-Rib", "Grand Beam", "2-1/2 in. Corrugated", "Alu-Loc", "Climaguard", "Shelterguard", "5-Rib", "2 1/2 " SSR", "4" rib", "Alpha Panel", "Decor-Flush", "Deep Rib II", "Deep Rib IV", "Delta Rib", "Fabrib", "High Seam", "HR-36", "IP Seam 3", "IP Snap 3", "PBU Panel", "PowerSeam", "Proclad", "R-Panel", "Select Series 12", "Select Series 612", "StrongClad", "U Panel", "Val Rib III", "Grandcurve N", "Powerseam II", "PBR Panel", "1-1/2 SSR 150", "1-1/4 Corrugated", "Alu-Twin", "Duralap", "Horizon 16", "Horizon S", "Horizon S100", "Prime Rib", "Strong Rib", "Ultra-loc 16", "7/8 Corrugated", "8" Rib", "Grand Cap", "GrandCurve", "HR288", "LP12", "LP15", "LP25", "Posi-Lock Soffit", "Silhouette HCF Series", "Snap on Batten", "Snap on Seam", "T Rib", "Thin Seam", "Twin Fold", "TrustiRib" and "W-Panel".

Let's examine what these two ratings mean. First, the easier one is the UL2218 rating. The UL2218 test is a test to simulate hail impact. In order to pass this test a roof system must sustain an impact without penetrating the roof system or allowing it to leak due to the impact. It can, however, be dented by the impact. There are four levels of the test. Class 1 must resist a 1-1/4" diameter steel ball dropped from 12'. Class 2 must resist a 1-1/2" steel ball dropped from 14'. Class 3 must resist a 1-3/4" steel ball dropped from 17'. And Class 4, which we passed, must resist a 2" diameter steel ball dropped from 20'.

The class A fire rating in accordance with UL790 means roof coverings which are effective against severe fire exposure. According to UL, under such exposure, roof coverings of class A are not readily flammable and do not carry or communicate fire, afford a fairly high degree of fire protection to the roof deck, do not slip from position, possess no flying brand hazard, and do not require frequent repairs in order to maintain their fire resistance properties. In other words, our panels are noncombustible. This class A rating, however, is not an hourly fire rating. Metal panels conduct heat very easily and do not provide any kind of hourly rating. To obtain an hourly rating it requires layers of fire rated gypsum board or a similar product. Class A panels, however, can also be applied over an hourly fire rated system without violating the hourly rating.

A copy from UL's website of our approval is attached.

[Home](#) [Quick Guide](#) [Contact Us](#) [UL.com](#)



Technical Bulletin

No	730
Page	2 of 3
Date	10/07/2016

TGFU.R9288 Roofing Systems

Roofing Systems

[See General Information for Roofing Systems](#)

FABRAL INC
3449 HEMPLAND RD
LANCASTER, PA 17601-1317 USA

R9288

OTHER SYSTEMS

Class A

Coated steel and aluminum panels identified as "AT Panel", "Grandrib 3", "Grandrib 3 PLUS", "1-1/2 in. SSR", "AVALON", "Slim Seam", "Stand'N Seam", "Mighti-Rib", "Ultra-Rib", "V-Crimp", "Hefti-Rib", "Grand Beam", "2-1/2 in. Corrugated", "Alu-Loc", "Climaguard", "Shelterguard", "5-Rib", "2 1/2 " SSR", "4" rib", "Alpha Panel", "Decor-Flush", "Deep Rib II", "Deep Rib IV", "Delta Rib", "Fabrib", "High Seam", "HR-36", "IP Seam 3", "IP Snap 3", "PBU Panel", "PowerSeam", "Proclad", "R-Panel", "Select Series 12", "Select Series 612", "StrongClad", "U Panel", "Val Rib III", "Grandcurve N", "Powerseam II", "PBR Panel", "1-1/2 SSR 150", "1-1/4 Corrugated", "Alu-Twin", "Duralap", "Horizon 16", "Horizon S", "Horizon S100", "Prime Rib", "Strong Rib", "Ultra-loc 16", "7/8 Corrugated", "8" Rib", "Grand Cap", "GrandCurve", "HR288", "LP12", "LP15", "LP25", "Posi-Lock Soffit", "Silhouette HCF Series", "Snap on Batten", "Snap on Seam", "T Rib", "Thin Seam", "Twin Fold", "TrustiRib" and "W-Panel".

1. **Deck:** NC **Incline:** Unlimited **Impact:** 4

Insulation (Optional): — Polyisocyanurate/composite, polyisocyanurate, glass fiber, perlite or wood fiber, any thickness.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15, 20 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

2. **Deck:** C-15/32 **Incline:** Unlimited **Impact:** 4

Barrier Board: — 1/4 in. min G-P Gypsum DensDeck® or 1/2 in. min UL Classified gypsum board with all joints staggered a min of 6 in. from the plywood joints .

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.



Technical Bulletin

No	730
Page	3 of 3
Date	10/07/2016

3. **Deck:** NC **Incline:** Unlimited **Impact:** 4

Insulation (Optional): — Polyisocyanurate board or polyisocyanurate composite board, any thickness.

Barrier Board (Optional): — 7/16 OSB or 5/8 in. plywood.

Ply Sheet (Optional): — Any UL Classified Type G1, G2 or G3 base/ply sheet, Type 15 or 30 felt or UL Classified prepared roofing accessory or GCP Applied Technologies Inc. "Ice and Water Shield".

Surfacing: — Steel or aluminum roofing panels, mechanically fastened.

[Last Updated](#) on 2016-10-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".