



A CLASSIC DESIGN FEATURING VALUE AND BEAUTY

Horizon S® is ideal for residential, post frame, and light commercial projects; the Horizon S® panel offers value with performance. Longevity and aesthetic appeal are essential when investing in your home. This standing seam panel with a snap-lock design features standard shadow lines to enhance the appearance of this panel.

GALVALUME (AZ50) WARRANTY COVERAGE

| | |
|----------------|----------|
| FILM INTEGRITY | LIFETIME |
| CHALK & FADE | 30 YEARS |
| PERFORATION | 20 YEARS |



SCAN FOR COLOR
AVAILABILITY

RECOMMENDED
PITCH:

3:12
AND ABOVE

GAUGE:

26

- 16" Coverage with 1" Seam Height
- UL 790 Class A Fire Resistance Rating
- UL 2218 Class 4 Hail Impact Resistance
- UL 580 Class 90 Uplift Test Rating
- High Performance WeatherXL SMP Paint System
- Nail Flange System for Faster installation
- Factory Applied Sealant
- Shadow Lines Standard to Enhance Appearance
- Custom Cut to Lengths from 5' up to 40' *
- Must be installed Over Solid Decking
- Strippable Film for Protection in Shipping
- To Reduce the Likelihood of Oil Canning, Install an Ethofoam Backer Rod Under the Center of the Panels Prior to Installation

* Profile configuration, color options, minimum and maximum lengths may vary by region, contact Fabral for availability.



SERVING THE
INDUSTRY



LOCAL CUSTOMER
SUPPORT



ENDURING
WARRANTY



TOTAL SYSTEMS
SOLUTION



WEATHER
RESISTANT



PANEL SPECIFICATIONS



A CLASSIC DESIGN FEATURING VALUE AND BEAUTY

Horizon S® is ideal for residential, post frame, and light commercial projects; the Horizon S® panel offers value with performance. Longevity and aesthetic appeal are essential when investing in your home. This standing seam panel with a snap-lock design features standard shadow lines to enhance the appearance of this panel.

| | | |
|---|---|---------------------------------------|
| SCREWS | SOLID | PLYWOOD |
| #10 x 1" Sharp Point Wafer Head Square Drive | Decking & Weather Barrier | Screw Spacing 12" Center to Center |
| OSB or ZIP SYSTEM® | NOT RECOMMENDED | |
| Screw Spacing 6" Center to Center | Installing Over Purlins or Existing Shingles | |



SERVING THE
INDUSTRY



LOCAL CUSTOMER
SUPPORT



ENDURING
WARRANTY



TOTAL SYSTEMS
SOLUTION



WEATHER
RESISTANT