



### DESIGNED FOR DURABILITY TO WITHSTAND EXTREME WEATHER CONDITIONS

With a deep continuous box design, the Prime Rib® panel adds character to post frame applications. Manufactured for durability, the Prime Rib® panel will stand up to most extreme weather conditions including wind, rain and snow.

WARRANTY COVERAGE		
	(G90) GALVANIZED	(AZ50) GALVALUME
FILM INTEGRITY	LIFETIME	LIFETIME
CHALK & FADE	30 YEARS	30 YEARS
PERFORATION (WALLS)	25 YEARS	20 YEARS
PERFORATION (ROOF)	20 YEARS	20 YEARS

RECOMMENDED PITCH:	<b>2½:12</b> AND ABOVE	GAUGE:	<b>29 or 26</b>
--------------------	---------------------------	--------	-----------------

- 33" Coverage with 1/2" Rib Height
- UL 790 Class A Fire Resistance Rating
- UL 2218 Class 4 Hail Impact Resistance
- High Performance WeatherXL SMP Paint System
- Custom Cut to Lengths up to 40'\*

\* Profile configuration, color options, minimum and maximum lengths may vary by region.



SCAN FOR COLOR AVAILABILITY



SERVING THE INDUSTRY



LOCAL CUSTOMER SUPPORT



ENDURING WARRANTY



TOTAL SYSTEMS SOLUTION



WEATHER RESISTANT




## DESIGNED FOR DURABILITY TO WITHSTAND EXTREME WEATHER CONDITIONS

With a deep continuous box design, the Prime Rib® panel adds character to post frame applications. Manufactured for durability, the Prime Rib® panel will stand up to most extreme weather conditions including wind, rain and snow.


*Actual metal samples are available; request samples prior to installation. Due to product improvements, changes and other factors, Fabral reserves the right to change or delete information here-in without prior notice.*

### PANEL SPECIFICATIONS



<b>110 SCREWS</b>	<b>OSB or PLYWOOD</b>	<b>PURLINS</b>
PER SQUARE RECOMMENDED	#14 x 1" Woodtite Type 17	#10 x 1½" HLX Type 17

### SCREW PATTERN



ALL SUPPORTS



SERVING THE INDUSTRY



LOCAL CUSTOMER SUPPORT



ENDURING WARRANTY



TOTAL SYSTEMS SOLUTION



WEATHER RESISTANT