



PRODUCT DESCRIPTION

Acceptable Product: Décor Flush II
 Class 4 Impact: UL2218
 Class A Fire: UL790

MATERIAL TABLE

Material	Panel Width	Coil Width	Weight/Sq. Painted
22 ga.	12"	15.75"	161.6 lbs.
24 ga.	12"	15.75"	127 lbs.
0.032"	12"	15.75"	58.48 lbs.
0.040"	12"	15.75"	72.9 lbs.

DESIGN INFORMATION

- Maximum Application Length Recommended: 6'
- Panel Length: Maximum - 25' Minimum - 6'
- Standard Panel Width: 12"
- Adjustable Reveal up to 1"
- In-line Venting Available in Aluminum
- Stiffening Ribs Available (with 1 or 2 ribs)
- Consult Fabral for Other Available Widths or Configurations

PRODUCT INSTALLATION

Décor Flush II panels are recommended for siding, fascias, or soffits only. When used for wall applications, Décor Flush II should only be installed vertically. Install panels plumb, level and straight so it is watertight and without waves or other distortions, allowing for thermal movement considerations. Apply sealant tape or caulking as necessary at flashing and panel joints to prevent water penetration.

WARRANTY INFORMATION

Fabral provides a 30 year paint-finish warranty for cracking, chipping, peeling, fading and chalking providing confidence in a long-lasting application. To ensure the durability of your Décorflush II panels, use proper care. Remove filings, grease, stains, marks or excess sealants from roof panels system to prevent staining. Store panels and flashings in a safe, dry environment.